

# Fierastrau circular de masa 1.650W, 255mm



## LS1040

Putere absorbită:	1650W
Turație în gol:	4600min <sup>-1</sup>
Blocare ax:	
Capacitate de tăiere la 0°:	93 x 95mm
Capacitate de tăiere la 45°:	93 x 67mm
Control constant al vitezei:	
Duză pentru aspirator:	
Nivel presiune acustică:	91dB(A)
Nivel putere sonoră:	101dB(A)
Nivel vibrații :	2,5m/s <sup>2</sup>
Diametru pânză/ exterior:	255mm
Diametru pânză/ interior:	30mm
Dimensiuni (L x l x H):	267x86x267mm
Lungime cablu alimentare (m):	2,5m
Greutate (EPTA) (kg):	11,0kg



- Frână de motor.
- Reglarea unghiului de tăiere până la 45°.
- Duză pentru conectarea unei instalații de aspirație pentru praf.
- Carrying handle's are convenient for transportation.
- Easy to Read Angle Scale
- Movable sub fence Material can be held widely by turning sub fence to right side.
- Rigid arm Accurate cutting can be performed.
- Blocking mechanism at the rest position (for European countries only) Locked at the upper position automatically, released by actuating the lever
- More efficient chip/sawdust collection. Less ejection toward operator